

DN16 - DN160 CF-F

INFICON 供应各种工业用观察窗，凡需要观察窗的应用均可安装。

供应的观察窗有：

- 硼硅玻璃
- kodial 玻璃
- 蓝宝石玻璃

我们的装配线还提供 ISO-KF / ISO-K / ISO-F 和 CF 法兰设计。



益处

- 保护窗口
- 以铁镍合金为转换材料
- 2011/65/EU RoHS 符合

订购信息


类型	DN 16 CF-F	DN 40 CF-F	DN 40 CF-F (sapphire glass)	DN 63 CF-F	DN 100 CF-F	DN 160 CF-F
Sapphire sight-glass DN 40 CF-F			214-032			
Screw set for sight glass DN16CF,6pieces	213-416					
Sight glass DN 100 CF-F					214-024	
Sight glass DN 16 CF-F	214-021					
Sight glass DN 160 CF-F						214-025
观察镜片 DN 40 CF-F		214-022				
视窗DN 63 CF-F				214-023		

规格


类型		DN 16 CF-F	DN 40 CF-F	DN 40 CF-F (sapphire glass)	DN 63 CF-F	DN 100 CF-F	DN 160 CF-F
真空连接		DN 16 CF-F	DN 40 CF-F	DN 40 CF-F	DN 63 CF-F	DN 100 CF-F	DN 160 CF-F
窗口		kodial glass	kodial glass	sapphire glass	kodial glass	kodial glass	kodial glass
密封圈		iron/nickel	iron/nickel	iron/nickel	iron/nickel	iron/nickel	iron/nickel
法兰		stainless steel 304/1.4301	stainless steel 304/1.4301	stainless steel 304/1.4301	stainless steel 304/1.4301	stainless steel 304/1.4301	stainless steel 304/1.4301
烘烤温度	°C	400	400	400	400	400	400
密封度	mbar•L/s	5×10^{-11}	5×10^{-11}	5×10^{-11}	5×10^{-11}	5×10^{-11}	5×10^{-11}
压力 (绝对)							
最小	mbar	1×10^{-10}	1×10^{-10}	1×10^{-10}	1×10^{-10}	1×10^{-10}	1×10^{-10}
压力 (绝对)							
最高 400 °C	bar			1		1	
最大	bar	2	2	2	2	2	2
最高 400 °C	bar	1	1		1		1
窗口厚度	mm	1.5	3	3	3.5	6	8
重量	kg	0.04	0.24	0.35	0.85	1.4	2.8

尺寸

214-021



214-022



214-032




214-023




214-024



214-025



Mounting



www.inficon.com reachus@inficon.com

由于我们的持续产品改进计划，因此产品规格可能会有变更，恕不另行通知。
RateWatcher 是 INFICON 的商标。所有其他商标均为其各自所有者的财产。

(2016-08) © 2016 INFICON